

VIN CHIP™ CONSUMER PACK SUITABLE FOR ALL MOTORHOMES & CAMPERS

Your VIN CHIP™ pack contains:

- 2 x RFID Chips
- 10 x Tamper Evident Window Lozenges
- 1 x Gas Locker Label
- 1 x Master Window Label
- 1 x Lint free microfibre cloth



FITTING INSTRUCTIONS

Please read carefully before commencing installation, exercise caution when removing the protective film or backing material of the labels and lozenges as they contain security cuts and it is possible to damage the item.

Fitting the Electronic RFID Chip

When choosing a location for your chip, bear in mind that it must be capable of being read by a police scanner at 10m distance when traveling up to 85mph. The front and rear cupboards and wardrobes are potential locations for the application. Place one in the habitation and one in the cab area.

Determine your location for the chip, ensuring that you have a large enough area. Ensure the surface is clean and dry, remove the backing paper and firmly rub the chip onto the surface.

The Police need to be able to read the chip from outside the Motorhome. Where it is fitted to metal, the silver side of the RFID chip must be facing the external wall of the vehicle.

Fitting the Master Window Label

The Window Label is to be placed on the inside of the main entrance door to the habitation area, place on the door window, bottom left.

Using the Microfibre cloth, ensure that the area is dry and clean of dirt or grease.

Carefully remove the protective film of the label and firmly rub onto the window surface ensuring no air bubbles are present.

Fitting the Gas Locker Label

The Gas Locker Label is to be placed inside at the rear of the Gas Locker on the opposite side to the gas regulator.

Where there is no gas locker, this can be placed inside a wardrobe door.

Each Gas Locker Label is made of tamper evident material designed to chip upon any attempt at removal. Ensure the area is dry and clean of dirt and grease.

Carefully remove the protective film of the label and firmly rub onto the surface ensuring no air bubbles are present.

Fitting the Tamper Evident Window Lozenges

The Window Lozenges are to be placed on the inside of all non-opaque windows. Placing the lozenges uniformly in the bottom right hand corner of each window. Each Tamper Evident Lozenge is made of tamper evident material designed to chip upon any attempt at removal.

Using the Microfibre cloth, ensure that the area is dry and clean of dirt or grease.

Carefully remove the protective film of the label and firmly rub onto the window surface ensuring no air bubbles are present.

Once you have completed the installation of the pack, please call **VIN CHIP** on **0333 212 4746** or email business.support@vinchip.co.uk to inform us where the electronic RFID chip has been fitted.

Health & Safety for Lozenges & Labels: Your safety in fitting this kit is of paramount importance, fitting your VIN CHIP™ kit is a non-hazardous process providing you follow the instructions carefully. These products are neither hazardous nor toxic, labels and lozenges may produce an allergic reaction if not handled correctly. However, the following describes possible accidents due to incorrect handling of the product and first aid treatment for such accidents. Contact with eyes - This is not a hazardous substance. However, if the product has entered your eyes, wash eyes thoroughly with pure water for at least 15 minutes, and consult a doctor. Contact with skin - Wash your skin with cold or lukewarm water. If a rash develops or if there is any pain, consult a doctor. Inhaling - This product is solid, thus there is no chance of inhalation. Swallowing - This is not a hazardous substance. However, wash mouth roughly with pure water. If possible, put your finger into your throat to induce vomiting, and consult a doctor.

RFID Information: The RFID has a 6-month shelf life from purchase. Store in dark conditions +20°C / RH 50%, Solvent free permanent adhesive is used. The RFID chip is fairly fragile.

Security Label Information: Handle with care. Ideal Store condition is 10~30°C and humidity is 70%RH or less. Do not allow moisture and chemicals in contact with the product.